



Zatič z notranjim navojem.

Dowel pin with internal thread.

Obdelava:

Kaljeno, napuščeno, fino brušeno na toleranco m5. Površina je bronirana.

Material:

Orodno jeklo

Trdota:

HRC 60 +/- 2

Primer naročila:

Cilindrični zatič z notranjim navojem premera 6 mm in dolžine 50 mm:
Cilindrični zatič: DIN 7979 ø 6 x 50.

Finish:

Hardened, tempered and precision ground to ISO tolerance m5. The surface is burnished.

Material:

Tool steel

Hardness:

HRC 60 +/- 2

Order example:

The tapered dowel pin with internal thread 6 x 50 mm.
Cylindrical dowel pin DIN 7979 ø 6 x 50.

d	m6	4	5	6	8	10	12	13	14	16	20
r		4	5	6	8	10	12	13	14	16	20
d²		M 3	M 3	M 4	M 5	M 6	M 6	M 6	M 8	M 8	M 10
d³		3,3	3,3	4,3	5,3	6,4	6,4	6,4	8,4	8,4	10,5
t¹		4,5-6	4,5-6	6	8	10	10	12	12	12	16
t²	min	7-10	7-10	10	12	16	16	18	20	20	25
t³		0,8	0,8	1	1,2	1,2	1,2	1,2	1,2	1,5	1,5
a		0,4	0,5	0,8	1,0	1,2	1,6	1,8	1,8	2,0	2,5
C		1,3	1,7	2,1	2,6	3,0	3,8	3,8	4,0	4,6	6,0
L	js 15										
8					●						
10		●		●							
12		●	●	●							
14		●	●	●							
16		●	●	●	●						
18		●	●	●	●						
20		●	●	●	●	●	●				
24		●	●	●	●	●	●				
28		●	●	●	●	●	●	●	●	●	
32		●	●	●	●	●	●	●	●	●	●
36		●	●	●	●	●	●	●	●	●	●
40		●	●	●	●	●	●	●	●	●	●
45		●	●	●	●	●	●	●	●	●	●
50		●	●	●	●	●	●	●	●	●	●
55		●	●	●	●	●	●	●	●	●	●
60		●	●	●	●	●	●	●	●	●	●
70		●	●	●	●	●	●	●	●	●	●
80		●	●	●	●	●	●	●	●	●	●
90		●	●	●	●	●	●	●	●	●	●
100		●	●	●	●	●	●	●	●	●	●
120		●	●	●	●	●	●	●	●	●	●